



- NOTES:
 1. METHOD OF ASSY-ARC WELD
 2. APPLY (1) COAT BLACK PRIMER

REV	REVISIONS	APP
A	RENDED AND RETURNED ON CAD	
B	ADDED TOLS AND RECTANGULAR	
C	REV DIM STYLE PATTERN DIMS	AM
D	1/8 1/4 WAS 16 APPROX 25 7/8	
E	3 1/2 1/2 & 2 3/16 DIMS. ADDED	
F	ECN 12526 6/16/93	
G	RENDED BOTTOM HOLE PATTERN TO SAME	FM
H	ECN 14889 2/26/97	
I	REMOVED REAR EXTENSIONS, REPR	
J	WAS 30 NOW 27 1/16. BOWARD IS	FM
K	34 13/32 @ C-S WAS 34 1/2	
L	4729/95	
M	CHK. PRIMER FROM GRAY TO BLACK W	TM
N	ECN 001294 1/10/12	
O	ITEM #1 DESCRIPTION WAS	
P	34 X 3 3/16 THK PLATE	
Q	34 X 3 3/16 THK PLATE	
R	ECN 001055 7/14 8/10/12	JP

QTY	PART NO.	ITEM	DESCRIPTION
2	CHANNEL-FRT/RR	3	C6 X 8.2# CHANNEL
4	FILLER-TOP/BOTT.	2	2 X 19 1/2 X 3/16 THK. PLATE
2	SIDE-R/L	1	6 X 23 7/16 X 3/16 THK. PLATE

9945-098-001	ASSY P/N	STANDARD BAW STOCK COMMERCIAL TOLERANCES APPLY UNLESS OTHERWISE SPECIFIED - DECIMALS & 0.005 INCHES 1/2	
DEXTER LAUNDRY, INC. FAIRFIELD, IOWA			
NAME: BASE ASSY-FRAME, 1 PLACE			
MATERIAL:			USED ON WORK SHOP FIELD INSTALL
FINISH:			REFERENCE
SPECS.			
1 PLACE	ISSUED BY: B. MACK	CHECKED:	APP.
	DATE: 5/13/93		DWG. NO. 9945-098
	SCALE: 1/4		